



**CUSHMAN**

**MODEL: HAULER 800**  
**TYPE: GASOLINE POWERED TRUCK**  
**MODEL YEAR: 2012**  
**Part No.: 618841**



**PRODUCT SPECIFICATION**

**CONFIGURATION HIGHLIGHTS**

**Engine:** 13 hp (9.7 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge

**Electrical:** Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

**Drive Train:** Automatic, continuously variable transmission (CVT)

**Brakes:** Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system

**Transaxle:** Differential with helical gears, ground speed governor, forward/reverse

**Capacity:** Seating for 2 persons.

**PRODUCT OVERVIEW**

**Dimensions**

Overall Length	107 in (272 cm)
Overall Width	49.5 in (128 cm)
Overall Height (No Canopy)	46.5 in (118 cm) (Top of steering wheel)
Overall Height (With Canopy)	70.0 in (178 cm)
Wheel Base	65.5 in (166 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Gnd Clearance @ Differential	4.3 in (11 cm)
Cargo Box Width (inside)	44.5 in (113 cm)
Cargo Box Length (inside)	30.5 in (77 cm)
Cargo Box Depth (inside)	7.5 in (19 cm)
Cargo Box Capacity	5.9 cu ft (0.17 m3)
Cargo Box material	Roto-molded polyethylene

**Vehicle Power**

Power Source	4 Cycle 24.5 cu in (401 cc)
Valve Train	Single Cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Industrial Rated Dry Filter
Lubrication	Pressurized Oil System
Oil Filter	Spin-On
Cooling System	Air Cooled
Fuel Capacity	5.8 Gallon (22.0 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward - Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

**Performance**

Seating Capacity	2 Persons
Dry Weight	750 lb (340 kg)
Curb Weight	895 lb (406 kg)
Bed Load Capacity	500 lb (230 kg)
Vehicle load capacity	800 lb (360 kg)
Outside Clearance Circle	18.9 ft (5.76 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	Fwd - 17.0 mph ± 0.5 mph (27.4 kph ± 0.8 kph)
(Optional speed available)	Rev - 12.3 mph ± 0.5 mph (19.8 kph ± 0.8 kph)
Towing Capacity	720 lb (327 kg) max load

**Steering & Suspension**

Steering	Self-compensating reduction rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	Links 18 x 8.50 - 8 (4 Ply Rated)
Rear Tires	Turf Saver 20 x 10 - 10 (Load Range B)

**Body & Chassis**

Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection molded TPO
Rear Body & Finish	Steel. Base coat/clear coat
Standard Color	Hunter Green

*Some items shown may be optional equipment*



**CUSHMAN**

**OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)\***

Item	Std	Opt	Fld	Item	Std	Opt	Fld
<b>TIRES &amp; WHEELS:</b>							
<b>Front:</b>							
Links 18 x 8.50 - 8 (4 Ply Rated)	●			Hour Meter		●	
USA Trail 18 x 8.50 - 8 (Load Range C)		●		Unique Individual Key Switch		●	
Turf Saver 18 x 8.50 - 8 (Load Range B)		●		Canopy Handle			●
<b>Rear:</b>				<b>HAULING &amp; TOWING:</b>			
Turf Saver 20 x 10.0 - 8	●			1 7/8 in (48 mm) Ball (Rcvr Reqd)		●	
USA Trail 18 x 8.50 - 8 (Load Range C)		●		1 7/8 in (48 mm) Ball, Drop (Rcvr Reqd)		●	
Links 18 x 8.50 - 8 (4 Ply Rated)		●		2 in (5 cm) Receiver (Rear)		●	
Turf Saver 18 x 8.50 - 8 (Load Range B)		●		Angle (Rcvr Reqd)		●	
<b>COLORS:</b>				Angle, Drop (Rcvr Reqd)			
Body Color - Hunter Green	●			Clevis (Rcvr Reqd)		●	
Body Color - Ivory		●		Clevis, Drop (Rcvr Reqd)		●	
Body Color - Bright White		●		Gas Spring Assisted Load Bed		●	
Body Color - Yellow		●		Load Bed Delete		●	
Body Color - Orange		●		Power Dump (Electric)		●	
Custom Body Color		●		Trailer, Dump (Poly Bed)			●
<b>Seating:</b>				<b>WEATHER PROTECTION:</b>			
Seat Color - Tan		●		Sun Canopy (Top) Black			●
Seat Color - Oyster		●		Windshield Fold Down			●
Seat Color - Gray	●			Weather Enclosure, (3 Side, Top & Windshield Req'd)			●
Custom Seat Color		●		Windshield Flat			●
<b>OTHER PERFORMANCE:</b>				<b>TRANSAXLE:</b>			
Ash Tray		●		Limited Slip Differential		●	
Front Fascia & Brush Guard - Black		●		<b>VEHICLE CAB:</b>			
Front Hydraulic Disc Brakes		●		Steel Cab without doors (Tan):			●
Fuel, Gauge In Dash		●		Steel Cab without doors (White):			●
Glove Box Door (Locking) Driver Side		●		Steel Cab without doors (Custom Color):			●
Glove Box Door (Locking) Passenger Side		●		Vinyl Door Set			●
High Altitude Jetting 3 - 6K ft (900 - 1800 m)		●		Beacon, Amber (Cab Required)			●
High Altitude Jetting 6K + ft (1800 + m)		●		Defroster/Fan (Cab Required)			●
Spark Arrestor		●		Dome Light (Cab Required)			●
<b>ELECTRICAL:</b>				Doors (Steel) Tan (Cab Required)			
Brake Lights		●		Doors (Steel) White (Cab Required)			●
Headlights	●			Doors (Steel) Custom Color (Cab Required)			●
Headlights & Taillights		●		Doors (Vinyl) Tan (Cab Required)			●
Strobe Light		●		Mirrors (Cab Required)			●
Turn Signals with 4-Way Flashers		●		Strobe Light (Cab Required)			●
Work Lights		●		Switch Panel (Cab Required)			●
Work Lights with Strobe Light		●		Windshield Wiper (Cab Required)			●
<b>Miscellaneous:</b>				Work Light (Cab Required)			
12 Volt Outlet		●					
CE Kit		●					
DC Converter		●					
Heavy Duty Battery		●					
Horn	●						