

SG280 SLOPE MOWER

SHIBAURA



Explore the Engineering Edge

IHI GROUP

SG280 Slope Mower - Features

The **SG280** is designed for mowing on slopes in as much comfort as on the flat, and complies with health and safety regulations.

The Shibaura SG280 Slope Mower will make the maintenance of steeply sloping grassed areas a lot easier, safer and more comfortable for the operator on the flat or slopes with its tilting seat to compensate for the working angle

Optional functions for comfort, easy operation and manoeuvrability


High displacement, high output Shibaura N843 diesel engine that fulfills exhaust emission regulations - 1496cc engine of 28PS horse power

Excellent designed hydraulic drive system to minimise noise and maximise driveability

Low centre of gravity for stability and safety

Hydraulic deck lift & mower engagement levers is conveniently located at the right side of the seat for ease of use

Optional Road Light Kit



SG280 SLOPE MOWER SPECIFICATIONS

Model	SG280	
Drive System	Hydrostatic transmission 2 speed, Low 4WD, High 2WD	
Body Measurements	Overall Length (mm)	2495
	Overall width (mm)	1590
	Overall height (mm)	1200
	Wheel base (mm)	1500
	Tyre - Front, Rear	21 x 11.00 - 10, 21 x 11.00 - 10
	Track Width - Front (mm), Rear (mm)	1310, 1310
Ground clearance (mm)	To bottom of mower deck	140
	Tractor Unit (kg)	800
Weight	Complete with 62" Rear Discharge (kg)	930
Engine	Model	SHIBAURA N843
	Type	3-Cylinder water cooled diesel engine
	Capacity (cc)	1496
	Power (kw[ps]/rpm)	20.6 (28)/2500
Fuel Tank Capacity		26L
	Brake Mechanism	Drum Brake
Power Unit	Steering Mechanism	Hydraulic power steering
Travelling Speed	Forward (km/h)	L: 0-9 (4WD) H:0-18 (2WD)
	Reverse (km/h)	L: 0-6 (4WD) H:0-12 (2WD)
	Cutting Width (mm)	1600(62" Rear)/1524(60" Side)
	Cutting Height (mm)	25-102
	Number of Blades	3
Cutting Speed (Depends on conditions)		1 - 8 KM Per Hour
Optional Extras	Road Light Kit	
	Rubber deflector	
	62" Rear Discharge/60" Side Discharge deck	



* In conjunction with correct driver training, ground conditions & tyre pressures.

SHIBAURA

IHI Shibaura Machinery Corporation

HEAD OFFICE

BYGS Shinjuku Bldg 2-19-1 Shinjuku, Shinjuku-ku, Tokyo 160-0022, Japan

TEL: +81-(0)3-5312-9662 FAX: +81-(0)3-5312-9668

WEB: www.ihi-shibaura.com/english