



Free-Floating AERO CORE™ Deck



Elastopolymer Bumpers



Battery Box

		36"	48"	52"
MOWER	Cutting Height Range	1 – 5"	1 – 5"	1 – 5"
	Deck Lift System	Adjustable (¼" increments)	Adjustable (¼" increments)	Adjustable (¼" increments)
	Deck Construction	7 Gauge	7 Gauge	7 Gauge
	Blades (¼" thick, high-lift wings)	(2) 18"	(3) 16.5"	(3) 18"
	Blade Tip Speed (fpm at 3,584 rpm)	19,000	19,000	19,000
	Spindles 1" shaft with precision ball bearings Non thru-bolt design	Ductile Iron Housings	Ductile Iron Housings	Ductile Iron Housings
	Blade Clutch/Brake Maintenance-Free; Rated Heavy Duty	Warner™	Warner™	Warner™
	Discharge Systems	Side & Mulch	Side & Mulch	Side & Mulch
ENGINE	Makes Available	FS & FX Kawasaki™	FX Kawasaki™	FX Kawasaki™
	Horsepower Heavy duty air cleaner – FX only	FS600 – 18.5 FX600 – 19 ZT710 – 20.2	FX600 – 19 ZT730 – 23.5	FX600 – 19 FX691 – 22 ZT730 – 23.5
	Cylinders	2	2	2
	Starting	Electric	Electric	Electric
	Hour Meter	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™
TRACTOR	Operator Control	Quad Lever™ – Ball Bearing	Quad Lever™ – Ball Bearing	Quad Lever™ – Ball Bearing
	Hydro Pumps	Hydro-Gear™ 10 cc	Hydro-Gear™ 10 cc	Hydro-Gear™ 10 cc
	Wheel Motors	Hydro-Gear™ 12 cu in	Hydro-Gear™ 12 cu in	Hydro-Gear™ 12 cu in
	Fuel Capacity	5.5 gal.	5.5 gal.	5.5 gal.
	Drive Tires	18 × 8.5 –10	18 × 10.5 –10	18 × 10.5 –10
	Caster Tires	11 × 4 - 5 Flat-Free	11 × 4 - 5 Flat-Free	11 × 4 - 5 Flat-Free
	Speed Forward (mph)	8.2	8.2	8.2
	Speed Reverse (mph)	3.5	3.5	3.5
DIMENSIONS	Overall Length	74" (65.5")	72.25" (63.75")	72.25" (63.75")
	Overall Width Deflector Up (Down)	36.5" (49.5")	49" (62")	53" (66")
	Dry Weight (lbs)	800	875	885

Warranty 2-Year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer.

AVAILABLE NOW AT A WRIGHT DEALER NEAR YOU

For more information, call 301.360.9810 or find our dealer locator at wrightmfg.com/dealer-locator