



AERO CORE™ Deck



Stationary Bar



Caster Tires

		Small Frame		Large Frame		
		32"	36"	48"	52"	61"
MOWER	Cutting Height Range	1.75 – 4.5"	1.75 – 4.5"	1.25 – 5"	1.25 – 5"	1.25 – 5"
	Deck Lift System	Shims, fixed deck	Shims, fixed deck	Shims, fixed deck	Shims, fixed deck	Shims, fixed deck
	Deck Construction	7 Gauge	7 Gauge	7 Gauge - AERO CORE™	7 Gauge - AERO CORE™	7 Gauge - AERO CORE™
	Blades (1/4" thick, high-lift wings)	(2) 16.5"	(2) 18"	(3) 16.5"	(3) 18"	(3) 21"
	Spindles	Ductile Iron with durable seals	Ductile Iron with durable seals	Ductile Iron with durable seals	Ductile Iron with durable seals	Ductile Iron with durable seals
ENGINE	Makes Available	Kawasaki™ FS Recoil, Electric, and Kohler® Confidant options		Kawasaki™ FX and FS options		
	Hour Meter	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™	Digital, Service Alert™
	Operator Controls	Quad Lever™	Quad Lever™	Quad Lever™ Ball Bearing	Quad Lever™ Ball Bearing	Quad Lever™ Ball Bearing
	Hydro Pumps	Hydro-Gear® 10 cc	Hydro-Gear® 10 cc	Hydro-Gear® 12 cc with fans	Hydro-Gear® 12 cc with fans	Hydro-Gear® 12 cc with fans
	Wheel Motors	Hydro-Gear® 12 cu in.	Hydro-Gear® 12 cu in.	Hydro-Gear® 15 cu in.	Hydro-Gear® 15 cu in.	Hydro-Gear® 15 cu in.
	Fuel Capacity	5.5 gal.	5.5 gal.	5.5 gal.	5.5 gal.	5.5 gal.
TRACTOR	Drive Tires	18 × 6.5 - 8 (4 ply)	18 × 8.5 - 8 (4 ply)	20 × 10 - 8 (4 ply)	20 × 10 - 8 (4 ply)	20 × 10 - 8 (4 ply)
	Caster Tires	11 × 4 - 5 flat free	11 × 4 - 5 flat free	13 × 5 - 6 flat free	13 × 5 - 6 flat free	13 × 5 - 6 flat free
	Speed Forward (mph)	7.5	7.5	9.5	9.5	9.5
	Speed Reverse (mph)	4.3	4.3	5.5	5.5	5.5
DIMENSIONS	Overall Length	58"	60"	59.25"	59.875"	62.5"
	Overall Width Deflector Up (Down)	33.5" (45.5")	36.5" (48.5")	49" (61")	53" (65")	62" (74")
	Dry Weight (lbs)	640	650	850	870	1005

Many models are offered with rear discharge deck options. For current configurations and engine options see our online price sheet.

Warranty 2-Year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer.

AVAILABLE NOW AT A WRIGHT DEALER NEAR YOU

For more information, call 301.360.9810 or find our dealer locator at wrightmfg.com/dealer-locator