

Model		TG 6370. SS. Centre ROPS	TG 6370. IQ ROPS	TG 6370. IQ Cab.
Engine				
Engine performance	Net power @ 2600 rpm in KW	26.6	26.6	26.6
	Net power @ 2600 rpm in HP	36	36	36
Engine speed RPM		2600	2600	2600
Displacement cm ³		1.647	1.647	1.647
Number of cylinders		3	3	3
Fuel tank (l)		40	40	40
Gearbox variants				
Manual gearbox		manual		
Gears		F12/R12		
Reverse gear lever (shuttle shift, power shift)		Standard		
Clutch operated by pedal		Standard		
IQ direct shift gearbox			Manual/Auto	Manual/Auto
Gears			F24/R24	F24/R24
Reverse gear lever (shuttle shift, power shift)			Standard	Standard
Hydrostatic transmission (AHL version)				
Intermediate gearbox				
Number of gears (switching steps)				
Cruise control, electrically with memory function				
Max. forward speed*		18.6 mph (30 km/h)	20.5 mph (33 km/h)	20.5 mph (33 km/h)
Max. reverse speed* km/h		15.5 mph (25 km/h)	15.5 mph (25 km/h)	15.5 mph (25 km/h)
ISEKI Easy Drive System				
Differential lock		Standard	Standard	Standard
PTO shafts				
Safety circuit via oil bath multi-plate clutch		Standard	Standard	Standard
Soft start-up switch / power shift		Standard	Standard	Standard
Mid-PTO shaft		optional	Standard	Standard
	Rotational speed RPM	2000	1080/1500/2000	1080/1500/2000
Rear PTO shaft	Rotational speeds	2	3	3
	Rotational speed RPM	540/750	540/750/1000	540/750/1000
Hydraulics				
Lifting power	on the coupling point (kg)	1270	1270	1270
	610 mm behind coupling point (kg)	1150	1150	1150
Additional lifting cylinder (right)				
Lifting power control of 3-point rear power lift		Standard	Standard	Standard
Total pump capacity l/min		52,0	50.1	50.1
Working hydraulics l/min		32.5	31.3	31.3
Steering hydraulics l/min		19.5	18.8	18.8
Hydraulic pressure bar		157	157	157
Position control		Standard	Standard	Standard
Joystick valve		optional	Standard	Standard
Additional hydraulic valves x 2 PCs (ES/DS switchable)		Standard	Standard	Standard
Equipment				
Suspension seat (multi-adjustable)		Standard	Standard	Standard
Comfort seat, pneumatic (multi-adjustable)		optional	optional	optional
Air-conditioning unit at rear of cabin				Standard
Towing hitch, drawbar at rear		Standard	Standard	Standard
Height-adjustable towing jaw with 30s bolt (trailer hitch ball coupling)		optional	optional	optional
Safety-tested fully glazed cabin, tinted windows				Standard
Hot water heater				Standard
Dimensions & weights				
Overall length mm		3195	3195	3195
Overall width mm		1290-1750	1290-1750	1290-1750
Height mm **		2200-2265	2595	2220-2280
Wheelbase mm		1770	1770	1770
Ground clearance** mm		310-395	310-395	310-395
Empty weight** kg		1525-1583	1525-1583	1640-1723
Gross vehicle weight kg		3200	3200	3200
Trailer weight braked (jaw coupling) kg		5000	5000	5000
Trailer weight braked (trailer hitch ball coupling) kg		3500	3500	3500
Trailer weight unbraked (jaw trailer hitch ball coupling) kg		2000	2000	2000

* With the largest tyres ** Depending on the tyres

