

RTM Fine turf maintenance equipment



The RTM **Eco-Spread** - for sport, pastures and estates



- Chequer-plate welded steel application roller for even spread of a range of materials
- Adjustable application rate through simple hand adjusters
- Low ground pressure turf wheels and tyres transfer drive through a simple drive mechanism
- Welded steel hopper with hydraulic action: "lower to load" and "lift to spread"
- Three point linkage mounting
- Parking stand
- Heavy duty greasable roller and agitator bearings
- HP requirement 25HP and above.
- Counterbalance may be required, as will a double acting spool valve.



Load and go

Simple one-tractor operation

- Wheel-driven spreading system that allows the operator to load and spread using the same tractor.
- Load and transport materials
- Spread a range of dry top dressings, sand and soils



Jackstand

Feed adjustment



Specifications

Height : 1.48m
Depth : 1.15m
Width : 2.35m

Working width : 1.38m
Weight : 380 kg
HP Requirement : 25+hp

R T Machinery Ltd

Hill Farm Buildings - Nether Winchendon
Aylesbury - Buckinghamshire - HP18 0DX
T: 01296 738197
E: sales@rtmachinery.co.uk
W: www.rtmachinery.co.uk



R T M reserve the right to update or amend the specifications and build of the RTM Eco-Spread through investment in constant research, development and improvement.