



TLE RANGE

High power and lift capacity,
simple controls, premium
economy range with same
unrivalled quality and reliability



QUALITY THAT'S BUILT TO LAST


WWW.ISEKI.CO.UK

TLE Range

QUALITY HIGH PERFORMING PREMIUM ECONOMY TRACTOR

The premium economy range of quality ISEKI built tractors feature high horse power and simple controls making them excellent value for money. All of this whilst offering the same unrivalled ISEKI reliability, high lift capacity and performance.

TLE tractors can be used on a wide range of applications, from smallholders to sport pitches, with spacious operator platforms, lift capacity of up to 1200 kg and optional pick-up hitch (55hp model) without compromising on quality, reliability or functionality.




Perfect for multi-users the easy to operate tractor is available in two models, the 40hp TLE3410 with hydrostatic or mechanical transmission or the 55hp TLE4550 with mechanical transmission for the ultimate control.

POWER AND PERFORMANCE


Perfect for a wide range of tasks the TLE3410 is powered by a reliable high capacity 1,826cc 3-cylinder, 40hp diesel engine. For increased power and capability the TLE4550 is run by a 2,434cc, 4-cylinder, reliable 55hp diesel engine.

Both engines offer efficient operation at 2,600rpm for lower vibration and noise levels for improved operator comfort whilst also causing less wear and tear on the engine itself.



HIGH LIFT CAPACITY

With a lift capacity of 1,200kg at the ball ends for the TLE4550 and 1,000kg for the TLE3410, the Category 1, 3 point linkage allows this range to easily run a wide range of implements from mower decks through to sprayers, aerators, rotavators and harrows.



EASY TO USE HST

Simple and easy to use, the TLE3410 HST is driven by a 3 range hydrostatic transmission. Ideal for where you have multiple users operating a tractor, or where fitted with a loader, it is effortless whilst maneuvering, constantly changing speed and direction.



OR THE ULTIMATE CONTROL OF A MANUAL

The TLE4550 and TLE3410 are built with a mechanical transmission for the ultimate control of speed. This is perfect for powering ground engaging equipment like aerators when speed control is essential to ensure the implement performs at its best.

TLE Range

FRONT LINKAGE

As an additional extra a front linkage can be added and/or PTO allowing a snow plough or brush to be mounted and used in inclement weather. Capable of running a huge range of equipment, the TLE range is invaluable all year round for a wide range of applications.



LIGHT FOOTPRINT

Thanks to its compact design and light footprint the TLE causes minimal turf damage, whilst the high lift capacity allows the use of numerous rear mounted and PTO driven equipment.



ROAD HOMOLOGATION

Lighting, indicators, side mirrors and parking brake are fitted as standard for safe and legal road use once registered.



MID PTO

Available on the TLE4550 as an additional option a Mid PTO at 2,000rpm can be fitted in order to run additional implements such as a mid mount mower deck or power a front PTO ensuring the tractor is used to its full capabilities.

DRAFT CONTROL

In order to utilise the TLE4550 for ploughing Draft Control can be fitted offering a truly multifunctional compact tractor capable of powering a wide range of equipment.

REAR PTO

The TLE range is manufactured complete with a single speed 540rpm rear PTO with standard and soft start for safe and easy use when powering implements.

Stationary PTO control is supplied as standard allowing you to run equipment such as chippers or saw benches in a safe and controlled manner.



OPTIONAL LOADER

Loader kits are available for the TLE range with either standard or parallel lift booms. A Third Function can be added to control buckets or forks with grabs for extra functionality.

The TLE3410 can come fitted with a MX C3 loader.

The TLE4550 has the option of a MX C4 loader.



HYDRAULICS

Equipped with 1 double acting spool valve as standard, an additional valve can be added where required for further functionality, such as controlling the lifting and folding of a trailed gang mower or the offset control of a rear-mounted flail.

AVAILABLE IMPLEMENTS INCLUDE

- 1.2m or 1.4m standard bucket (1.6m standard bucket for TLE4550)
- 1.2m 7-tine manure forks with or without grab
- Pallet forks with or without a rear frame and grab
- Twin bale spikes
- 1.3m multiservice bucket
- 1.4m 4-in-1 bucket



TLE Range

ASSISTED FOLDABLE ROPS

The tractor is manufactured with certified and approved ROPS to ensure the safety of the operator is paramount.

Where the ROPS need to be lowered in order to access storage areas it is fitted with an assisted ram to help take the weight whilst folding down and raising up again.



COMFORTABLE WORKING

For long periods working on the tractor the low levels of vibration minimize operator fatigue. This is due to the high torque low revving engine. The flat spacious operator comfort gives maximum space and comfort whilst operating or getting on and off the machine. ISO Mounted platform for the ultimate comfort is standard on the TLE4550.



EASY ACCESS FOR SERVICING & MAINTENANCE

Simple to open and close, the hinged bonnet and clip fit side panels offer excellent easy access to perform regular maintenance checks on the engine and service points.



ERGONOMIC CONTROLS

All the controls fall easily to hand when in the driving seat with motion controls, range and PTO selectors all located on the left hand side. All the hydraulic controls including the auxiliary valve levers and rear linkage are located on the right hand side to ensure the tractor and its implements are effortless to control.



TYRES TO SUIT TERRAIN

Whether you require your tractor for fine turf applications or to tackle farmland there is a tyre to suit your needs.

TLE Range - TECHNICAL SPECIFICATION

MODEL	TLE3410 HST & MECH	TLE4550
POWER		
Engine Type	Turbo Diesel E3FH	Turbo Diesel E4PFH
Emission controls	Stage V, DPF, EGR, DOC	Stage V, DPF, EGR, DOC
Displacement	1,826cc	2,434cc
No of cylinders	3	4
Power	29.4kW (40hp)	40kW (55hp)
Fuel Capacity	40 ltr	53ltr
Rated Engine Speed	2600rpm	2600rpm

TRANSMISSION	HST	Mechanical	
Type	3 range HST	Mechanical	Mechanical
No of Speeds	3 forward, 3 reverse	8 forward, 8 reverse	12 forward, 12 reverse

PTO		
Type	Independent, engine driven	Independent, engine driven
Control	Controlled by PTO Selector Lever	Controlled by PTO Selector Lever
Rear PTO	540 PTO min-1@2,455 min-1 engine speed	540 PTO min-1@2,430 min-1 engine speed
Mid PTO (optional)	N/A	2,000 PTO min-1@2,714 min-1 engine speed

BRAKES		
Type	Wet Multi Disk	Wet Multi Disk

TYRES	Turf, Ag or Wide Ag	Turf or Ag
Front	212/80D15 (turf) 7-16 (Ag) 240/70R16 (Wide Ag)	29x12.00-15 (turf) 9.5-16 (Ag)
Rear	355/80D20 (turf) 11.2-24 (Ag) 320/70R24 (Wide Ag)	475/65D-20 (turf) 13.6-24/28 (Ag)

HYDRAULICS		
Hydraulic output	Main 28.3L/min, Steering 13.9L/min	Main 32.15L/min, Steering 19.35L/min
Rear linkage type	3-point hitch	3-point hitch
Rear linkage size	Category 1	Category 1
Lift capacity	1,000kg at ball end, 810kg 24" behind	1,200kg at ball end, 1,100kg 24" behind
Aux valve	1 std, 2nd optional	1 std, 2nd optional

ELECTRICAL		
Charging	45 amp alternator with internal regulator/rectifier	45 amp alternator with internal regulator/rectifier

DIMENSIONS		
Length	3.07m	3.45m
Width	1.49m Turf, 1.43m Ag	1.69m Turf, 1.59m Ag
Height	2.61m Turf, 2.63m Ag	2.54m Turf, 2.65m Ag
Weight	1,300kg Turf, 1,375kg Ag	1,78kg Turf, 1,810kg Ag
Wheelbase	1.675m	1.98m
Ground clearance	0.24m Turf, 0.25m Ag	0.24m Turf, 0.34m Ag



TLE RANGE

Don't just take our word for it.

Try an ISEKI tractor for yourself and book a demonstration with your local dealer.

**Contact us today
01473 599266**

 **ISEKI**

QUALITY THAT'S BUILT TO LAST

