

TH5420/ TH5370



To get the most from your investment you need to be able to use your tractor for a multitude of jobs. The new Stage V compliant TH range from ISEKI fits the bill perfectly - designed for versatility, maximum comfort and ease of use.

The tractor has a 2-speed rear PTO with 2 mode engagement and auto-stop function, plus a mid PTO to suit a variety of implements.

The 3 speed hydrostat allows easy control of the tractors transmission to suit many tasks in conjunction with the standard cruise, memory and response control.

You can work in the ultimate comfort with the air conditioned cab. The steering wheel can be adjusted to suit each operator.



KEY FEATURES

Power: 40hp & 35hp

Lift capacity: 1,200kg at ball end

Special features: Soft-start PTO, advanced hydrostatic transmission and comfort with the option of a cab, ISO mounted operators platform

		TH5420	TH5370
Power	Engine: Type	Diesel E3CD InDirect Injection OHV	Diesel E3CG InDirect Inj OHV
	Aspiration	Turbo	Turbo
	No of cylinders	3	3
	Power	29.4kW (40hp)	25.7kW (35hp)
	Fuel capacity	36ltr	36ltr
	Rated engine speed	2600rpm	2600rpm
Transmission	3 Range	3 range HST	3 range HST
	Gear speeds	3 gears forward, 3 reverse	3 gears forward, 3 reverse
	Steering	Power Steering	Power Steering
Brakes	Type	Wet discs	Wet discs
	Tyres	Type	Turf or Ag
	Front	24 x 8.5-12- PR (turf) 7-14 4PR (ag)	24 x 8.5-12- PR (turf) 7-14 4PR (ag)
	Rear	315/80D-16-6PR (turf) 9.5-24 4PR (Ag)	315/80D-16-6PR (turf) 9.5-24 4PR (Ag)
PTO	Type	Independent, engine driven	Independent, engine driven
	Clutch	Hydraulically engaged, multi-plate wet disc	Hydraulically engaged, multi-plate wet disc
	Rear PTO Shaft	540 PTO min-1@ 2,484 min-1 engine speed	540 PTO min-1@ 2,484 min-1 engine speed
		540/750(540e)rpm-1@ 2,291 min-1 engine speed	540/750(540e)rpm-1@ 2,291 min-1 engine speed
	Mid PTO Speed	2000rpm @ 2500rpm	2080rpm@ 2600rpm
		Speed @ ers: 1,507 @ 2,600 min-1	Speed @ ers: 1,595 @ 2,600 min-1
		Speed @ ers: 1,921 @ 2,600 min-1	Speed @ ers: 2,004 @ 2,600 min-1
Hydraulics	Hydraulic output	Total: 41.5, Main 29.2L/min, Steering 12.3L/min	Total: 41.5, Main 29.2L/min, Steering 12.3L/min
	Rear linkage type	3-point hitch	3-point hitch
	Rear linkage size	Category 1	Category 1
	Lift capacity	1,200kg at ball end, 730kg 24" behind	
Charging	CAB Type	80 amp alternator with internal regulator/rectifier	
Dimensions	Length	3.1m	
	Width	1.35m Cab, 1.14m ROPS	
	Height over ROPS	2.16m Cab, 2.495m ROPS	
	Weight with ROPS	1490kg Cab, 1250kg ROPS	
	Wheelbase	1.685m	