

SF2 Range - Technical Specifications

MODEL	SF224	SF237
POWER		
Engine Type	ISEKI E3112-XG02	ISEKI E3CD-VG04
Displacement	1123cc	1826cc
No of cylinders	3	3
Power	22.5hp	35hp
Fuel Capacity	40ltr	40ltr

TRANSMISSION		
Type	HST	HST
Front Axle	Standard	Standard
Steering system	Power Steering	Power Steering
Driving system	Auto or 4WD	Auto or 4WD

PTO		
PTO	Front	Standard
Mower	Clutch type: Wet Disk independent	Clutch type: Wet Disk independent
Revolution	2000@2600min-1 (rpm)	2000@2600min-1 (rpm)
Blower	Clutch type: Wet Disk independent	Clutch type: Wet Disk independent
Revolution	2100@2600 min-1 (rpm)	2650@2600 min-1 (rpm)

BRAKES		
Type	Dry Drum	Dry Drum
Parking Brake	Lever	Lever
Differential Lock Type	Standard	Standard

TYRES	Turf	Turf
Front	23 x 10.5 12	23 x 10.5 - 12
Rear	18 x 8.5 - 8	18 x 8.5 - 8

MOWER DECK	Rotary (both)	MU-FM Flail (both)	ISEKI Flail Mulch (SF224 only)	Rotary Collection (Both)	Rotary (SF237 only)	MU-Collect (SF237 only)
No of Blades	3	M-Flails 24	Y-Flails 30 pairs	2	2	M-Flails 24
Discharge	Rear	Mulching	Mulching	Rear Collection	Rear Collection	Rear Collection
Cutting Width	60"	1.4m	1.37m	54"	60"	1.4m
Cutting Height	25-125mm	>130mm	>125mm	25-120mm	25-120mm	>130mm
Adjustments	2 & 10 stages by pin replacement	Roller & Castor Wheels	Roller & Castor Wheels	2 & 10 stages by pin replacement	Pin & Single point or electric adj	Roller & Castor Wheels
Weight	205kg Linkage 20kg	229kg		105kg Linkage 20kg		223kg

Actual operating power output may vary due to conditions of specific use. NOTE: Specifications, while correct at time of printing, may change without notice.

SF2 Range - Technical Specifications

MODEL	SF224	SF237
COLLECTOR		
Model	SBC950	SBC950 F3
Capacity	950ltr	950ltr
Dump System	Hydraulic	Hydraulic
Height of Lift	2130mm	2250mm
Weight	160kg	160kg

DIMENSIONS		
Height	2,115mm	2,120mm
Width	1,245mm	1,245mm
Length	2,725mm	2,790mm
Wheelbase	1,275mm	1,375mm
Total Weight	870kg	1,060kg



Designed, engineered and built in Japan, the Iseki SF2 Range offers the greatest reliability, finest quality and outstanding performance.