

# ETESIA

Theoretical efficiency	3000 m <sup>2</sup> /h
Slope radiant	20°
Transmission	Hydraulic

## New ATTILA AK-60 and AH-75



NEW

The new Attila 60 and 75 pedestrian brush cutters are designed for work in the most difficult conditions. They are ideal for holiday homes, meadows, orchards, fallow land, roadsides and shores.

### EFFICIENCY

- Heavy-duty brush cutting (up to Ø30 with AH75 and Ø20 with AK60).
- Mowing on the most difficult slopes (up to 20° for AK60 and 30° for AH75) thanks to the hydraulic transmission with a differential lock.
- Two idlers that can be locked without a tool for improved stability on slopes in the AH75
- Possibility to fit two wider rear wheels as an option
- Cutting height adjustment with three positions from the handle: quick, convenient and safe
- Handle offset control from the operating position with three working positions and one transport position

### COMFORT

- Very high manoeuvrability thanks to the hydraulic transmission and the three forward speeds, one reverse speed and the differential effect.
- The differential lock can be engaged without interrupting movement
- All the operating controls are available from the operating position for convenience and safety
- Protection for controls and hands with the guards incorporated into the handle with a three-position adjustment facility
- Central handle that allows easier access to low controls (parking brake, forward transmission bypass, engine starter), with full protection for cables (no visible cable)
- Parking brake for safe immobilisation
- Anti-vibration rubber handles

### RUGGEDNESS

- The machine can be moved into the vertical position to gain access to the cutter blade for maintenance and cleaning.
- Maintenance-free hydrostatic transmission with forced-air cooling, integrated expansion vessel
- Flail blades: reversible, protect the blade transmission system, low maintenance costs
- Rugged and reliable engines: Engine crank shaft mounted on bearings, cast iron jacket for better

AK-60   
AH-75

**2**  
YEARS  
WARANTY

Of professional  
use

Rugged and manoeuvrable,  
to offer you peerless efficiency !

**3**  
YEARS WARANTY  
OF PRIVATE USE



Drive wheels with an agricultural profile for improved adherence



Ergonomic and safe handle



Rugged and reliable engine

Dimensions and weight	AK-60	AH-75
Height (cm)	114	114
Width (cm)	77	85
Length (cm)	210	213
Mass (kg)	129,5 full/125 empty	150,5 full /148 empty

Engine	AK-60	AH-75
Engine	Kawasaki FJ180V OHV	Honda GXV 390 OHV
Engine power	3,3 kW	7,3 kW
Capacity	180 cm <sup>3</sup> - 3300tr/min	390 cm <sup>3</sup> - 3000tr/min

	AK-60	AH-75
Working width	60 cm	75 cm
Working height	3 positions	
Differential lock	Yes	
Forward transmission	Hydraulic	
Speeds	FW : 0 to 5 km/h REV : 0 to 2 km/h	
Theoretical efficiency*	3000 m <sup>2</sup> /h	3750 m <sup>2</sup> /h

\*Theoretical efficiency = maximum mowing speed x cutting width



**ETESIA**

www.etesia.com